



Angloco

Anglo 10400 Foam Tender



OUTLINE SPECIFICATION

Chassis & Crew Cab Scania P94GB6x4NZ. GVW: 26,000 kg.
Engine: 310 hp (228 kW).
Gearbox: fully automatic.
Crew cab with seating for 6 (driver plus five).
Sit-and-strap BA brackets for the rear crew.

Fire Engineering

Water Tank 1,350 litre stainless steel.
Foam Tank 9,050 litre stainless steel.
Water Pump Multi-pressure gunmetal centrifugal pump, nominally rated at 5,000 litre/min @ 8 bar. High pressure output for the hose reel.
Foam System Automatic balanced pressure system. Single variable flow fixed rate proportioner.
Foam Pump Gear pump, rated at 300 litre/min @ 14 bar.
Hose Reel One manual rewind hose reel, with 54m of 19mm hose, fog gun, foam tube and inductor.

Monitor Manually operated dual barrel water/foam monitor. 360° rotation. Nominal rating 3,300 litre/min at 10 bar.

Bodywork Heavy duty aluminium modular construction, with two lockers per side plus rear pump bay, all enclosed by aluminium alloy roller shutters. Recessed monitor operator's platform with fixed and folding safety rails. Access ladder. Sliding cradle, drawers, & adjustable shelves.

Standard Accessories Full width light bar, and emergency siren. Front and rear halogen repeater lamps. Pneumatically extending floodlight mast. Automatic inlet pressure reducing valve, to protect the pump. Automatic output pressure controller.

Finish Fully painted to customer's specification.

Options/Variations To meet individual customer requirements.

Full specifications available on request