



# Angloco

## Water/Foam Carrier – 11500



### Summary Details

- Chassis:** MAN TGA 26.350 6x4BL. 26,000 kg GVW. 350 hp (257 kW). Automated shift manual transmission. MAN two door medium cab for three persons.
- Water Tank:** 8,500 litre, stainless steel, vacuum type.
- Foam Tank:** 1,000 litre, stainless steel, for "Class A" type foam concentrate.  
2,000 litre, stainless steel, for "Class B" type foam concentrate.
- Installed Equipment:** Aluminium alloy centrifugal water pump, rated at 2,000 litre/minute at 7 bar. Integrated CAFS to provide Compressed Air Foam discharge. Electronically controlled foam proportioning system for Class A or B foam, with electric motor driven rotary gear foam pump delivering up to 12 litres/minute of foam concentrate, and water flow sensor to ensure injection of the correct amount of concentrate. Change-over valve to enable selection of A or B foam. Capable of 0.3% ratio for Class A foam at 2,000 litres/minute solution flow rate, to 3% ratio for Class B foam at 400 litres/minute solution flow rate. Two delivery outlets for water discharge. Two delivery outlets for water/CAF discharge. One normal pressure hose reel, 50 m x 33 mm, electric rewind, mounted on swing-out frame, for discharge of water/CAF. Vacuum/exhauster pump, PTO/hydraulically driven, nominally 1,000 litre/minute fill/empty rate, providing alternative water tank fill/empty facility. Foam transfer pump, PTO/hydraulically driven, up to 300 litres/minute.
- Superstructure Bodywork:** Heavy duty aluminium modular construction, featuring low level side locker, front transverse locker, plus rear pump bay and lockers module, all enclosed by aluminium alloy roller shutter doors. Low level side access to suction hose stowage in enclosed trays. Safety railing for roof level maintenance walkway, pneumatically operated.
- Accessories:** Full width light bar on cab roof. Siren system. LED repeater lamps at front, sides and rear. Scene lamps at sides and rear. Data logging system.