



Anglo 15000 Special Purpose Trailer Tanker



OUTLINE SPECIFICATION

Trailer Chassis	High strength self-supporting construction, low height, combined tank/trailer assembly, comprising two bogies, each with tandem axles. Each bogie is mounted via a turntable, enabling the trailer to be towed from either end, with the rearmost bogie automatically locked straight. Each bogie is fitted with a spring supported draw bar, and the trailer features two sets of braking and lighting systems. Fully laden mass approx. 20,000kg.	Water Pump	Dual pressure centrifugal cast iron water pump, with bronze impeller. Driven by a close coupled independent petrol engine. Pump performance nominally rated at 2,000 litre/min @ 7 bar, or 100 litre/min @ 24 bar. Two 63.5mm deliveries. One outlet to the hose reel.
Fire Engineering		Bodywork	Two low level aluminium alloy lockers provided each side, with hinged doors, providing stowage space for tools and rolled lengths of delivery hose. Access ladder and tank top catwalk. Ventilated enclosures for pump engine and batteries.
Water Tank	15,000 litre stainless steel construction 2m diameter cylindrical water tank, with internal baffles and circumferential reinforcing rings. Two manholes, filler cap, hydrant fill inlet, two 102mm outlets, valved outlet to water pump, sight tube level gauge.	Finish	Fully painted to customer's requirements.
Hose Reel	One high pressure manual rewind unit, located above the pump at the rear, with 54m hose and jet/spray branchpipe.	Options/ Variations	To meet individual customer requirements.

Full specifications available on request

Angloco Limited Station Road, Batley, West Yorks., England WF17 5TA. Tel: +44 (0) 1924 441212
Main Fax: +44 (0) 1924 471918 Sales and Service Fax: +44 (0) 1924 424703

The Company is quality assessed to BS EN ISO 9001