



Angloco

Water Tender - 1800



OUTLINE SPECIFICATION

Chassis & Crew Cab

MAN 15.225 LRC 4x2
Engine: 220 bhp (162 kW).
Gearbox: manual or automatic.
GVW: 15,000 kg.
Large crew cab with seating for total of six.
Sit-and-strap BA brackets for four crew.

Fire Engineering

Water Tank 1,800 litres.

Water Pump Multi-pressure light alloy centrifugal pump, nominally rated at 4,000 litre/min @ 7 bar. High pressure output for the hose reels. Central suction connection. Four rear facing screw-down delivery valves. Automatic primer. Pump located in the rear pump bay, which is enclosed by two vertically hinged doors.

Hose Reels Two powered rewind units, located one each side at the rear, each with 3 x 18m lengths of high pressure hose, terminating in a fog gun.

Bodywork

Heavy duty aluminium alloy construction, fully interfaceted to protect against electrolytic corrosion. Three lockers each side, enclosed by aluminium alloy roller shutters. Transverse forward internal stowage section to carry a short extension ladder and other long items. Swing-out shelves and slide-and-tilt shelves. Stowage for 10.5 m or 13.5 m extension ladder, short extension ladder, roof ladder, suction hose, delivery hose, branch pipes, hydraulic rescue equipment, floodlighting, etc.

Standard Accessories

Full width light bar; siren/PA system; repeater lamps front and rear; battery charger; air compressor; portable water pump; floodlighting mast c/w 3 x 500 W lamps; 110 V generator; front mounted electric winch; search light; full complement of fire fighting and rescue equipment.

Finish

High quality paint and reflective markings.

Full specifications available on request