



Angloco

Water Tender / Pumping Appliance - 1800



Chassis & Crew Cab

Volvo FL250 4x2 chassis.
Rear air suspension.
Engine 250 hp, 950 Nm, Euro 6.
Allison AL306 automatic transmission with retarder.
16,000 kg GVW
Volvo crew cab with air conditioning.
Seating for 2 + 4.
SCBA brackets for four crew members.
Full-width stowage module for crew.

Water Tank

1800 litre capacity. Auto fill regulation.

Foam Tank

50 litre capacity for Class A foam.

Water Pump & Foam System

PTO-driven Godiva PC2A 2010.
Three normal delivery outlets.
One dedicated CAFS delivery outlet.
Electronically controlled foam proportioning system.
Compressed Air Foam System CAFS.

Hose Reels

Two pneumatic rewind high pressure hose reels, each with 60 m of 22 mm bore hose.

Superstructure

Angloco Pumping Appliance.

Body

Copolymer body construction.
Galvanised steel subframe.
Six side lockers with roller shutters.
Pump compartment with hinged doors.
Central locking system.
Stowage gantries for ladders.
Slide-out trays and slide-and-tilt trays.

Electrical

CAN-bus control system. Electronic siren.
LED lightbar. LED repeater lamps.
Headlamp flasher. LED scene lamps.
Floodlight mast with 2 x LED lamps.
Electric winch. Mains powered battery charger with auto-eject connector.
CCTV system.