



Angloco

Light Pumping Appliance – 300



OUTLINE SPECIFICATION

Chassis & Cab Land Rover Defender 130 DC HCPU 4x4.
90 kW (120 bhp) 2.4 litre turbo diesel engine.
Six speed manual gearbox.
Two speed transfer box.
3,500 kg GVW Heavy Duty Suspension.
Land Rover double cab for up to five (1+4).

Bodywork Based on the standard Land Rover aluminium High Capacity Pick-Up body. Full width transverse locker, with two aluminium alloy shutter doors, each with lift bar latch. Roof gantry for ladder and suction hose.

Fire Engineering

Water Tank 300 litre capacity.

Water Pump Independent centrifugal aluminium alloy water pump driven by close-coupled petrol (gasoline) engine. Electric start, with manual back-up. Wide pressure range performance, from 350 litre/minute at 7 bar to 115 litre/minute at 20 bar. Valve to control output to hose reel or a normal pressure delivery outlet with 2.5" instantaneous coupling.



Hose Reel 45 m x 19 mm, manual rewind, with high pressure jet/spray water branch pipe.

Accessories Two-tone air horns; emergency warning beacon; officer's spot lamp; 6.3 m extension ladder; 2 x suction hose; suction strainer; controlled two-way dividing breeching; 5 x 20 m delivery hose; 2 x selectable flow jet/spray water branch pipe; dry powder extinguisher; carbon dioxide extinguisher.