



# Angloco

## Bronto Skylift F32RLER Aerial Ladder Platform



### SUMMARY SPECIFICATION

Bronto's pioneering combined telescopic aerial ladder platforms have proven themselves as versatile and reliable appliances with fire services throughout the world. The unit features all the regular benefits of the Bronto including: zero tail-swing, up-and-over capability, high capacity water-way, continuous rescue ladder, and high capacity rescue cage with water monitor.

**Chassis & Cab** Mercedes Benz Econic 2633 - 6x2\*4  
GVW: 26,000 kg.  
Engine: 326 bhp (240 kW).  
Gearbox: automatic  
Single cab with seating for 2 (driver plus one).

### Fire Engineering

**Water Way** Integrated continuous water way provided to the cage mounted monitor, with 3,800 litres/minute capacity. Rear inlet connections for water supply to the vehicle.

**Monitor** Remote controlled water monitor mounted at the cage, together with two separate delivery outlets plus hose reel at the cage.

**Bodywork** Fully enclosed co-polymer plastic bodywork with aluminium alloy roller shutter doors enclosing locker compartments. Substantial stowage space. Enclosed jack board lockers and top decking safety railings.

### Telescopic Hydraulic Aerial Ladder Platform

**Height:** Maximum working rescue height of 32 m.  
**Reach:** Horizontal reach of 22.5 m at 400 kg cage load.  
**Capacity:** Cage/platform capacity of 400 kg.  
**Platform:** Large well equipped rescue cage/platform, suitable for four persons. Easy and safe entry and exit access. Collision protection guard device, and water spray protection curtain.

**Ladder:** Continuous integrated rescue ladder to base.  
**Stabilisers:** H-type jacking system, operable from the ground via extended wander-lead.

**Controls:** Platform operation from cage or turntable.  
Option available: radio remote control.

**Rotation:** 360 degree continuous rotation.

**Safety:** Comprehensive systems and backup pump.

**Accessories** LED blue roof light system. LED repeater lamps front and rear. Ladder and jack lighting systems. Platform auto-lubrication system. 110 Volt Dynaset generator with floodlamps on the cage. GSM service access modem.