



Angloco

Bronto Skylift F32RLER Aerial Ladder Platform



SUMMARY SPECIFICATION

Bronto's pioneering combined telescopic aerial ladder platforms have proven themselves as versatile and reliable appliances with fire services throughout the world. The unit features all the regular benefits of the Bronto including: zero tail-swing, up-and-over capability, high capacity water-way, continuous rescue ladder, and high capacity cage with water monitor.

Chassis & Cab MAN TGS 26.400 6x2-2 BL.
GVW: 26,000 kg.
Engine: 400 bhp (294 kW).
Gearbox: automated manual.
Single cab with seating for 2 (driver plus one).

Fire Engineering

Water Way Integrated continuous water way provided to the cage mounted monitor, with 3,800 litres/minute capacity. Rear inlet connections for water supply to the vehicle.

Monitor Remote controlled water monitor mounted at the cage, together with two separate delivery outlets at the cage.

Bodywork Fully enclosed co-polymer plastic bodywork with aluminium alloy roller shutter doors enclosing locker compartments. Substantial stowage space.

Telescopic Hydraulic Aerial Ladder Platform

Height: Maximum working rescue height of 32 m.
Reach: Horizontal reach of 22.5 m at 400 kg cage load.
Capacity: Cage/platform capacity of 400 kg.
Platform: Large well equipped rescue cage/platform, suitable for four persons. Easy and safe entry and exit access. Collision protection guard device, and water spray protection curtain.

Ladder: Continuous integrated rescue ladder to base.
Stabilisers: H-type jacking system, operable from the ground via extended wander-lead.

Controls: Platform operation from cage or turntable.
Option available: radio remote control.

Rotation: 360 degree continuous rotation.
Safety: Comprehensive systems and backup pump.

Accessories LED blue roof light system. LED repeater lamps front and rear. Ladder and jack lighting systems. Platform auto-lubrication system. 110 V generator with floodlamps on the cage.