



Angloco

Bronto Skylift F32RLER Aerial Ladder Platform



SUMMARY SPECIFICATION

Bronto's pioneering combined telescopic aerial ladder platforms have proven themselves as versatile and reliable appliances with fire services throughout the world. The unit features all the regular benefits of the Bronto including: zero tail-swing, up-and-over capability, high capacity water-way, continuous rescue ladder, and high capacity rescue cage with water monitor.

Chassis & Cab	Volvo FM 380, 6x2*4 - mid-steer, pusher axle. GVW: 26,000 kg. Engine: 380 hp (283 kW). Gearbox: 5 speed automatic. Low roof sleeper cab with seating for 2 in total.	Telescopic Hydraulic Aerial Ladder Platform	Height: Maximum working rescue height of 32 m. Reach: Horizontal reach of 22.5 m at 400 kg cage load. Capacity: Cage/platform capacity of 400 kg. Platform: Large well equipped rescue cage/platform, suitable for four persons. Easy and safe entry and exit access. Collision protection guard device, and water spray protection curtain.
Fire Engineering		Ladder:	Continuous integrated rescue ladder to base.
Water Way	Integrated continuous water way provided to the cage mounted monitor, with 3,800 litres/minute capacity. Rear side inlet connections for water supply to the vehicle.	Stabilisers:	H-type jacking system, operable from the ground via extended wander-lead.
Monitor	Remote controlled water monitor mounted at the cage, together with two separate delivery outlets at the cage.	Controls:	Platform operation from cage, turntable or ground based radio remote control.
Bodywork	Fully enclosed co-polymer rear bodywork with aluminium alloy roller shutter doors enclosing comprehensive stowage compartments.	Rotation:	360 degree continuous rotation.
		Safety:	Comprehensive systems and backup pump.
		Accessories	LED blue roof light system. LED repeater lamps front and rear. Ladder and jack lighting systems. Platform auto-lubrication system. High output 24 volt floodlamps on the cage.