



Angloco

Hose/Foam Carrier – 3650



OUTLINE SPECIFICATION

Chassis & Cab MAN TGM 18.340 4x4 BB. 340 hp (250 kW) diesel engine. Automatic transmission. 18,000 kg GVW. Air conditioned large MAN crew cab with seating for six persons. SCBA brackets for four rear crew.

Fire Engineering 3,400 litre foam tank, stainless steel. 425 litres/minute PTO-driven foam pump. 250 kg dry powder unit, two delivery outlets.

Installed Equipment 8.5 m height floodlighting mast with 8 x lamps. Electric winch with 25 m wire rope. Portable foam transfer pump.

Bodywork Specialist bodywork superstructure, with aluminium roller shutters enclosing upper compartments, and hinged doors for lower compartments forming steps when opened. Four removable pull-out rear cabinets/trays to carry a total of 36 lengths of 30 m delivery hose. Two extending platforms at the rear. Two swing-out access ladders at the rear.

Equipment/ Accessories Light bar, LED type. 2 x rear beacons, LED. Electronic siren/PA system. Two-tone horns. Side and rear scene lamps. Four spot lamps. Reversing video device and parking sensors. Intercom. PPV fan, electric motor driven. Portable generator, 5 kVA. Extension ladder.

