



Angloco

Compact Water Tender - 450



OUTLINE SPECIFICATION

- Chassis & Cab** Mercedes-Benz Sprinter 519CDI 4x2 chassis. 3 litre V6 turbocharged and intercooled diesel engine, 190 bhp/140 kW. Manual gearbox. Four door double cab.
- Bodywork** Aluminium construction. Two lockers per side, each enclosed by a roller shutter door. Two hinged rear doors enclosing the pump compartment. Specialised stowage facilities provided for fire fighting and rescue equipment, including fixed, sliding, and slide-and-tilt shelves, stowage for 10.5 m and 6.3 m extension ladders, and suction hose.
- Fire Engineering**
- Water Tank** 450 litre, polypropylene construction.
- Water Pump** Multi-pressure light alloy centrifugal pump, nominally rated at 1,000 litre/min @ 7 bar. High pressure output for the hose reel. Central suction connection. Two rear facing screw-down delivery valves. Automatic primer. Built-in two-way collecting head.
- Hose Reel** One powered rewind unit, located within a side compartment, with 30 m of 19 mm high pressure hose, terminating in a fog gun.



- Accessories** Two LED mini light bars; warning siren system; blue LED repeater lamps at the rear, front, and front intersection; four side mounted LED scene lamps; officer's lamp; battery charger with mains input connector; floodlight mast. Reflective tape applied to sides and rear.