



Angloco

Light Water Tender - LRX 450



OUTLINE SPECIFICATION

Chassis

Land Rover Defender 110 Pick-Up 4x4.
Engine: 111 bhp (83 kW) turbocharged diesel.
Gearbox: 5 speed manual.
Transfer box: 2 speed.
GVW: 3,050 kg.

Bodywork

Based on the standard Land Rover Defender aluminium pick-up body. Full width transverse locker constructed from alloy, located behind the cab, with two anodised aluminium roll-up shutter doors. Roof gantry for ladder and two suction hose.

Fire Engineering

Water Tank 450 litre. Hot dip galvanised steel.

Cab

Standard Land Rover cab for two (1 + 1).
Centre seat for occasional third person.

Water Pump Single stage light alloy centrifugal pump, nominally rated at 2,270 litre/min at 7 bar when drawing from open source via suction. Driven from engine via mechanical PTO. Central suction connection. Two rear facing screw-down delivery valves. Automatic primer. Illuminated control panel at the rear pump bay.

Accessories

Rotating warning beacon (red or blue).
Two-tone horns. Officer's spot lamp.
Two 2.4m lengths of 102mm suction hose.
Suction strainer, basket and wrenches.
Rolled lengths of fire fighting delivery hose.
Two adjustable jet/spray water branch pipes.
6.4m triple extension aluminium ladder.
Two-way collecting head. Hand held extinguisher. Vehicle tool kit.

Hose Reel One manual rewind unit, located above the pump at the rear, with 2 x 17 m lengths of 25 mm bore hose, and jet/spray branch pipe.

Full specifications available on request