



Angloco

Foam Tender – 6000



Summary Details

- Chassis:** MAN 18.285 MRC 4x2. 18,000 kg GVW.
280 hp (206 kW). Automatic transmission.
Two door long cab with seating for two persons (driver plus one).
- Foam Tank:** 6,000 litre (comprising 6 x 1,000 litre ISO containers), plus 200 litre training tank.
- Installed Equipment:** Six water inlet connections (for supply from hydrant or supporting vehicle).
Water motor driven piston foam-dosing pump, providing automatic foam proportioning at 3 percent or 6 percent solution mix.
Electronically controlled and programmable remote operated water/foam monitor located at the roof, rated at 2,500 litre/minute.
PTO driven foam concentrate transfer pump, rated at 400 litre/minute.
Screen wash deluge system.
- Superstructure Bodywork:** Three lockers per side: one each side enclosed by anodised aluminium alloy roller shutters; two each side enclosed by hinged doors.
Securing system for locating each foam container, enabling rapid removal and replacement by a fork-lift truck.
Roof monitor operator's recessed working platform, with two access ladders.
Adjustable shelves and hose stowage trays.
- Accessories:** Full width light bar on cab roof, and at rear. Siren with Public Address system.
Side mounted hazard lamps.
24 V electric motor driven foam transfer pump, 50 litre/minute.