



# Angloco

## Water/Foam Tender – 7000



### OUTLINE SPECIFICATION

<b>Chassis &amp; Crew Cab</b>	Mercedes-Benz 1828A/45 Atego 4x4 chassis. Engine: 279 hp (205 kW). Gearbox: 12 speed manual. GVW: 19,000 kg Fully tilting safety crew cab for six persons.
<b>Fire Engineering</b>	
Water Tank	6,000 litre. Stainless steel construction.
Foam Tank	1,000 litre. Stainless steel construction.
Water Pump	Multi-pressure aluminium centrifugal pump, nominally rated at 3,500 litre/min @ 10 bar. Four 63.5mm deliveries. 140mm suction inlet. Automatic pump output pressure controller.
Hose Reels	Two manual rewind hose reels, located one each side at the rear, each with 54m of 19mm bore hose, and high pressure fog gun.
Monitor	Manually controlled water/foam monitor located on the roof, rated at 2,400 litre/min at 10 bar.

<b>Foam System</b>	Automatic around-the-pump proportioning system, with settings for 3, 4, or 6% mix.
<b>Bodywork</b>	Heavy duty aluminium modular construction, with two lockers per side plus rear pump bay, enclosed by aluminium alloy roller shutters. Interface materials used to protect against corrosion. Access ladder to the roof. Fold-down steps assist access to front lockers. Shelves and stowage facilities for equipment.
<b>Standard Accessories</b>	Emergency warning beacons. Rear repeater lamps. Siren/PA system and two-tone horns. Battery charger. Search light, cable reel and tripod. Delivery hose. Jet/spray branch pipes. Suction hose, strainer, basket and wrenches. 10.5m triple extension aluminium ladder. Officer's spot lamp. Complete sets of fire service breathing apparatus. Torches. Rescue tools and equipment.
<b>Finish</b>	Fully painted to customer's requirements.