



# Angloco

## Multi-Media Refinery Tender – 7300



### OUTLINE SPECIFICATION

**Chassis & Cab** Mercedes-Benz 3348 Actros 6x4. 476 hp (350 kW) diesel engine. "Telligent" automated shift gearbox. 33,000 kg GVW. Two door medium length cab with air conditioning and seating for three. Exhaust spark arrestor. Automatic engine air inlet shut-down valve.

### Fire Engineering

**Water Tank** 4,500 litre, GRP construction.

**Foam Tank** 2,300 litre, GRP construction.

**Water Pump** Bronze/gunmetal centrifugal multi-pressure pump, rated up to 7,500 litre/minute at 7 bar. Discharge to: roof monitor, 6 x 2.5" handline delivery outlets, 4 x 5" high volume delivery outlets, and high pressure to the hose reel.

**Foam System** Balanced pressure foam proportioning system, by-pass type, with individual metering valves for each of the normal pressure delivery outlets. Bronze rotary gear pump, for fill/transfer and foam proportioning.

**Water/Foam Monitor** Electronically controlled monitor rated at 6,000 litre/minute, with Hydro-Chem nozzle.

**Hose Reel** High pressure hose reel, with 54 m of 25 mm hose, terminating in a fog gun.



**Dry Powder Unit** 500 kg capacity unit, discharged through two 30 m hoses, each with trigger-operated nozzle, and through Hydro-Chem monitor nozzle.

**Bodywork** Aluminium construction with locker storage compartments and pump compartment enclosed by roller shutters. Custom stowage facilities for fire fighting and rescue equipment.

**Equipment / Accessories** Siren/PA system. Light bar, repeater lamps and side scene lamps. Telescopic floodlight mast. Winch. Battery master switch. Mains powered battery charger and brake air compressor. Extension ladders. Suction and delivery hoses. Branch pipes. Hydraulic and pneumatic rescue equipment. Transportable generator.