



Angloco

Multi-Media Refinery Tender – 8000



Summary Details

| | |
|--------------------------|---|
| Chassis: | Volvo FM9 6x4 chassis. 26,000 kg GVW. 340 hp. Automatic transmission. Four door crew cab with seating for six persons (driver plus five). |
| Water Tank: | 2,300 litre. |
| Foam Tank: | 5,500 litre. |
| Installed Equipment: | Multi-stage bronze / gunmetal centrifugal water pump, 6,000 litre/minute. PTO driven foam pump, rated at 360 litre/minute. Balanced pressure foam proportioning system, with single variable flow fixed rate proportioner. Manually controlled water/foam monitor located at the roof, rated at 4,000 litre/minute. One high pressure hose reel, featuring high pressure in-line foam induction unit, with 55 m hose and jet/spray fog gun. 180 kg capacity carbon dioxide extinguishing unit, provided with two discharge hose reels, each with 30 m hose and discharge applicator. |
| Superstructure Bodywork: | Three lockers per side plus rear pump bay, enclosed by roller shutters. Roof monitor operator's recessed working platform, with access ladder. Adjustable shelves and hose stowage trays. |
| Accessories: | Full width light bar, and emergency siren/PA system. Front and rear repeater lamps, plus side fend-off repeater lamps. Side mounted scene lamps. Headlamps alternating flasher. Pneumatically extending floodlight mast. Battery charger. Search lamp with cable reel. |