



Angloco

Light Pumping Appliance – 800



OUTLINE SPECIFICATION

Chassis & Cab Iveco 55S15DWH Daily 4x4.
107 kW (146 bhp) 3 litre turbo diesel engine.
Six speed manual gearbox with overdrive, plus two speed transfer box (total ratios: 24).
5,500 kg GVW.
Iveco Daily four-door double cab.

Bodywork Heavy duty aluminium alloy construction.
One locker each side, plus rear pump compartment, enclosed by aluminium roller shutters. Stowage for suction hose.
Internal shelving and stowage for equipment.

Fire Engineering

Water Tank 800 litre capacity, polypropylene construction.
Hydrant fill connection at the rear.
Tank level sight tube gauge.

Water Pump Aluminium alloy centrifugal pump, nominally rated at 1,500 litre/min at 7 bar.
Driven by the chassis engine via PTO.
Central suction connection. Two rear-facing screw-down delivery valves. Automatic primer.
Discharge output for the hose reel.



Hose Reel 55 m length x 25 mm bore, electric rewind, with jet/spray water branch pipe.

Accessories Siren with public address; emergency warning light bar; front and rear LED repeater lamps; front intersection LED repeater lamps; headlamp alternating flasher; four LED side scene lamps; officer's spot lamp; telescopic floodlight mast; 4.4 m extension ladder; portable extinguishers; front-mounted electric winch.