



Angloco

Targeted Response Vehicle - 800



OUTLINE SPECIFICATION

Chassis & Cab Mercedes-Benz Sprinter 515 4x2 high roof van. 150 hp turbocharged/intercooled diesel engine. Manual gearbox. 5,000 kg GVW. ABS & ASR. Original cab plus crew area arrangement providing seating for four persons (2+2). Stowage in rear area for two sets of SCBA.

Bodywork Based on the original M-B high roof panel van. Roller shutter door to the rear. Specialised stowage facilities for fire fighting and rescue equipment, including two slide-out trays, full width slide-and-tilt tray, slide-out cradle for a portable pump, and fixed stowage shelves.

Fire Engineering

Water Tank 800 litre, polypropylene construction.

Foam Tank 25 litre foam concentrate container.

Water Pump Ultra high pressure water mist system with PTO-driven piston type pump. 38 litres/min at 100 bar. Integral foam mixing system.

Hose Reel 60 m, electric rewind, with water/foam nozzle.

Portable Unit 250 litre/minute portable water pump.



Accessories Full width LED light bar; warning siren system; two-tone air horns; blue LED repeater lamps at front, sides and rear; red LED incident lamps at rear; headlamp flasher; map light; scene lamps to sides and rear; LED white and red interior lighting; door/shutter open indication in cab; central locking for doors and shutter; battery charger with mains connector; battery guard system; data logging unit; CCTV system; hand wash unit; hot drinks unit; reflective tape applied to sides and at rear.