



Angloco

First Intervention Vehicle – 9500



Summary Details

Chassis:	Scania P124GB6x4NZ. 26,000 kg GVW. 360 hp (265 kW). Automatic transmission. Two door regular cab with seating for two persons (driver plus one).
Water Tank:	4,000 litre.
Foam Tank:	5,500 litre, plus 200 litre training tank.
Installed Equipment:	Single stage bronze / gunmetal centrifugal water pump, 6,400 litre/minute. Pump-and-roll operation capability. PTO driven foam pump, rated at 515 litre/minute. Balanced pressure foam proportioning system, for up to 8% solution mix. Electronically controlled and programmable remote operated water/foam monitor located at the roof, rated at 4,000 litre/minute. Remote controlled water/foam bumper monitor, rated at 950 litre/minute. Two sideline delivery outlets, pressure regulated. Two powered rewind hose reels, each with 60 m hose and jet/spray fog gun. Five under-body protection nozzles, each 75 litre/minute. Ten hydrant water inlet connections. Pump and systems remote operation from either of three control panels.
Superstructure Bodywork:	Two lockers per side plus rear pump bay, enclosed by roller shutters. Roof monitor operator's recessed working platform, with two access ladders. Adjustable shelves and hose stowage trays. Fold-down steps assist access to front lockers.
Accessories:	Two red rotating warning beacons. Siren with Public Address system.