



Angloco

Light Pumping Appliance – 950



Summary Details

Chassis:	Mercedes-Benz Vario 816DA 4x4 chassis crew cab. 7,490 kg GVW. 156 hp (115 kW) turbocharged diesel engine. Manual gearbox transmission. Four door crew cab with seating for five persons (driver plus four).
Water Tank:	900 litre capacity.
Foam Tank:	50 litre capacity.
Installed Equipment:	PTO-driven multi-pressure aluminium alloy centrifugal water pump, rated at 2,000 litres/minute at 10 bar. Two normal pressure 2½" BS instantaneous delivery outlets, each with ball valve. 4" (102 mm) suction inlet. Two powered rewind high pressure hose reels, each with 3 x 18 m x 19 mm bore hose, terminating in a high pressure jet/spray branch pipe. High pressure foam induction system for each hose reel.
Superstructure Bodywork:	Aluminium alloy construction, with roller shutter doors enclosing lockers at each side. Hinged doors enclosing the pump compartment at the rear. Specialised stowage facilities provided for fire fighting and rescue equipment.
Accessories:	Full width LED light bar on cab roof. Emergency warning siren and public address system. Two-tone air horns. LED Repeater lamps at front and rear. Scene lighting. Alternating headlamp flasher. Mains electric powered automatic battery charger and brake air top-up compressor. Boost/jump start connector. Pneumatically extending telescopic floodlighting mast.