



Angloco

High Volume Pumping Unit / Hose Layer – 8000/1100



OUTLINE SPECIFICATION

Chassis & Cab MAN TGS 26.400 6x4 BL chassis. Automated manual transmission. 26,000 kg GVW. Two door cab with seating for driver plus one person.

Hooklift System Multilift demountable hooklift system. 21 tonnes capacity, Configured to suit both CHEM and DIN standard containers. In-cab controls.

Fire Engineering

Demountable Module Hytrans Duo Container incorporating hydraulically driven, power slide Hose Recovery Unit type HRU200. Storage cabinets for a range of Portable Water Supply Equipment. Mounting provisions for 2 x Demountable Containers.

Demountable Containers Transported on Duo Container and comprising:-
- HydroSub 150 hydraulically driven, portable, submissible pump – max 8,000 lit/min at 2.1 bar with 60m hydraulic hose reel assembly and recovery winch. Hydraulics powered by Deutz 6 cylinder diesel engine.
- Steel construction Hosebox carrying 1,100m of 152mm (6") dia. High Volume Water Supply Hose.



Portable Water Supply Equipment

A wide range of aluminium alloy gated manifold dividers, gated valves, Y- Pieces and hose ramps are provided, stored in the Duo Container cabinets.

Bodywork & Accessories

Plastic construction, chassis mounted locker box assemblies with roller shutter doors, providing additional stowage space. Front and rear LED warning light systems and reversing camera.

Options

Additional Hoseboxes with Water Supply Hose – require further Duo Container or additional vehicle movements.